

PJD5111

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH BRILLIANTCOLOR™ TECHNOLOGY

Easy to use, easy to afford

ViewSonic's PJD5111 is a practical projector that offers outstanding value and performance. This SVGA resolution projector supports high definition signals and projects 2500 lumens for clear, bright images in most lighting conditions. At only 5.1 pounds, it is light and compact, making it ideal for the mobile presenter or to move from room to room in the office or on a campus. Texas Instruments' BrilliantColor™ technology delivers brilliant, true-color and high contrast images for viewing presentations, charts, or video. With extensive connectivity, including two RGB inputs and one RGB output, the PJD5111 is an excellent multifunctional data/video projector. Eco-mode reduces fan noise for less distraction during important presentations and even extends the lamp life up to 4000 hours*. The PJD5111 is perfect for users looking for an easy to use, versatile and portable projector at a great price.



Versatile presentations anywhere

> BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.

> Bright in virtually any setting

Packs 2,500 ANSI lumens in just 5.1 lb, and with a high 2800:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

> Eco-mode extends lamp life

Extend the life of your lamp up to 4000 hours* and reduce noise output.

> Off to Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™

PJD5111

ViewSonic®
See the difference™ 

LIGHT, BRIGHT AND PORTABLE PROJECTOR



Optional Accessories

- >Replacement lamp RLC-047
- >Universal ceiling mount kit WMK-005
- >Wireless G presentation gateway WPG-150
- >2nd & 3rd year extended warranty PRJ-EE-03-03

Projection Distance 4:3 Screen		Screen Size 4:3 Screen	
M	feet	m	Inches
1.2	3.9	0.7~0.8	28.0~31.7
1.5	4.9	0.9~1.0	35.2~40.0
1.8	5.9	1.1~1.2	42.3~48.0
2	6.6	1.2~1.3	47.4~53.7
3	9.8	1.8~2.2	70.3~79.7
5	16.4	3.3~3.4	117.6~133.3
11.3	37.1	6.4~7.6	250~300



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	SVGA 800×600 (Native) / SXGA 1280×1024 (compressed)
	Lens	1.1× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Size	35"-155" / 0.89m-3.9m
	Throw Distance	1.5m-6m / 4.9ft-19.7ft / 59.05"-236.2"
	Throw Ratio	1.86:1-2.04:1
	Lamp	189 watt
	Lamp Life (Normal / Eco Mode)	3000 / 4000* hours
	Brightness	2500 Lumens
Contrast Ratio	2000:1 (typ), 2800:1 (dynamic)	
Aspect Ratio	4:3 (native) & 16:9	
Color Gamut	85 % NTSC 1931 CIE	
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 30-70 KHz, Fv: 50-87 Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac	Up to 832×624 (may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub
	RGB Output	1 × 15-pin mini D-sub
	Component	2 × 15-in mini -D-Sub (shared with RGB)
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1×RS-232 (8 Pin Mini-Din)
AUDIO	Speaker	1×5W
	Amplifier	1×1W
POWER	Voltage	90~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	242W (Typical) / <5W (Stand-by mode)
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	OSD	Display: Screen color, aspect ratio, keystone, position, phase, H. size, digital zoom Picture: Preset mode: brightest, standard (Video), daylight, ViewMatch (PC), cinema, user 1/user 2, brightness, contrast, color, tint, sharpness, BrilliantColor™, color temp., save settings Source: Quick auto search System setting (Basic): Language, projector position, auto power off, blank timer, panel key lock, timer controller, splash screen System setting (Advanced): Quick cooling, high altitude mode, DCR, active VGA out, audio settings, menu settings, closed caption, lamp settings, security setting, reset all settings Information: Current system status (source, preset mode, resolution, color system, equivalent lamp hour)
OPERATING CONDITIONS	Temperature	32°F-104°F (0°C-40°C)
	Humidity	10% - 90% (non-condensing)
	Altitude	0~6,000 ft (1,800m), operational up to 10,000 ft (3048m)
NOISE LEVEL	Normal / Eco Mode	30dB / 26dB
DIMENSIONS	Physical	10.4 × 3.8 × 8.86 (in) / 264 × 96.4 × 225 (mm)
	(W × H × D)	13.4 × 7.9 × 10.7 (in) / 340 × 190 × 273 (mm)
WEIGHT	Net	5.1 lb (2.3 kg)
REGULATIONS		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKRSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.

Rev.1.0

Sales: (888) 881-8781 · SalesInfo@ViewSonic.com · ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved [14323-01B-03/09] PJD5111-1

For more product information, visit us on the web at ViewSonic.com